




FD-4-3C
(standard)

Options

- **Factory-installed sleeve** ■ Integral
 - Gauge: ■ 20 (1.0) ■ 18 (1.3) ■ 16 (1.6) ■ 14 (2.0) ■ 10 (3.5)
 - Length: ■ 12" (305) ■ 16" (406) ■ 24" (610) ■ Other _____
- **Transitions:**
 - Round ■ Oval
 - Duct connections (sleeve required):
 - 1" (25) S-clip ■ DM-25 ■ DM-3 ■ WARD
- **16 ga. (1.6) retaining angle systems:**
 - Picture frame: ■ SSPF (single-side) ■ DSPF (2-sided)
 - Individual angle sets: ■ SS (single-side) ■ DS (2-sided)
- **Alternate fire closure temperature:**
 - 212°F (100°C)
- **Duct access door factory mounted in common sleeve**
- **Burglar Bars**
- **Type-304 stainless steel construction**
- **PI-10** (Blade closure indication switch package):
 - External mount (sleeve required) ■ Internal mount ■ Loose

The FD-4-3C fire damper employs curtain-style blades for point-of-origin control of fire in static HVAC systems. The FD-4-3C may be installed in vertical walls or partitions or horizontally in floors or assemblies with fire resistance ratings up to 4 hours.

Ratings

UL 555 Fire Resistance Rating: 3 Hour (vertical and horizontal)

UL HNLJ.V-5: Ventilation Duct Assemblies

Listings

UL 555 listing: R14981

CAN/ULC S112 listing: R14981

CSFM listing: 3225-1404:101

New York City MEA listing: 295-98-E

Meets NFPA Standards: 90A, 92A, 92B and 101

Meets Building Code Standards: IBC, NBC, NFPA, SBC and UBC



Standard Construction

Frame: 22 gauge (0.85) galvanized steel

Blades: 24 gauge (0.7) galvanized steel – curtain style


Fire Closure Device: Fusible link

Fire Closure Temperature: 165°F (75°C)

Minimum Size: Vertical Mount: 4" x 2" (102 x 51)
Horizontal Mount: 4" x 7" (102 x 178)

Maximum Size: Single Section: Vertical: 34" x 32" (864 x 813)
Horizontal: 36" x 32" (915 x 813)
Vertical: 106" x 20" (2692 x 508)
Multiple Section: Horizontal: 74" x 91" (1880 x 2311)

Stainless Steel: Single Section: Vertical: 34" x 20" (864 x 508)
Multiple Section: Vertical: 106" x 20" (2692 x 508)



* Damper dimensions furnished approximately 1/4" (6) undersize
† Damper dimensions furnished approximately 1/8" (3) undersize.
** See table on Page 3 for 'T' dimension

NOTE: Dimensions in parentheses () are millimeters.
Information is subject to change without notice or obligation.

Typical Damper Dimensional Data


FD-4-3C

3 Hour – Static Fire Damper
Curtain-Style Blade


* Damper dimensions furnished approximately 1/4" (6) undersize
† Damper dimensions furnished approximately 1/8" (3) undersize.

Round Transitions
(Standard with $D=W=H$.
Available with $D<W$ and H)


Oval Transitions
(Standard with W and H equal to
damper width and height dimensions.
Available with W and H smaller than
damper width and height)



Style CR (Optional)




Sleeve Style CO (Optional)




Sleeve Style C (Optional)

** See table on page 3 for 'T' dimension


Blade Stack Dimensional Layout



Framed Unit — No Sleeve
(Multiple section units supplied as individual
dampers for field assembly)



Sleeve Style S — Common Sleeve
(Multiple section units supplied as a single assembly)



Sleeve Style IS — Integral Sleeve

Blade Stack Dimensional Data Sizing Chart

FD-4-3C

3 Hour – Static Fire Damper
Curtain-Style Blade

Damper Width

Nominal Duct Height 'H'	Damper Width	
	Galvanized Vertical Mount: 4"(102) - 36"(914) Galvanized Horizontal Mount: 6"(152) - 36"(914)	Galvanized Vertical Mount: 4"(102) - 36"(914) Galvanized Horizontal Mount: 6"(152) - 36"(914)
2"(51)	5"(127)	5"(127)
3"(76)	6"(152)	6"(152)
4"(102)	7"(178)	7"(178)
5"(127)	8"(203)	8"(203)
6"(152)	9"(229)	9"(229)
7"(178)	10"(254)	10"(254)
8"(203)	11"(279)	11"(279)
9"(229)	12"(305)	12"(305)
10"(254)	13"(330)	13"(330)
11"(279)	14"(356)	14"(356)
12"(305)	15"(381)	15"(381)
13"(330)	16"(406)	16"(406)
14"(356)	17"(432)	17"(432)
15"(381)	18"(457)	18"(457)
16"(406)	19"(483)	19"(483)
17"(432)	20"(508)	20"(508)
18"(457)	21"(533)	21"(533)
19"(483)	22"(559)	22"(559)
20"(508)	23"(584)	24"(610)
21"(533)	24"(610)	
22"(559)	26"(660)	
23"(584)	27"(686)	
24"(610)	28"(711)	
25"(635)	29"(737)	
26"(660)	30"(762)	
27"(686)	31"(787)	
28"(711)	32"(813)	
29"(737)	33"(838)	
30"(762)	34"(864)	
31"(787)	35"(889)	
32"(813)	36"(914)	
33"(838)	38"(965)	
34"(864)	39"(991)	
35"(889)	40"(1016)	
36"(914)	41"(1041)	
37"(940)	42"(1067)	
38"(965)	43"(1092)	
39"(991)	44"(1118)	
40"(1016)	45"(1143)	
41"(1041)	46"(1168)	
42"(1067)	47"(1194)	
43"(1092)	48"(1219)	
44"(1118)	49"(1245)	
45"(1143)	50"(1270)	

Damper Width

Galvanized Horizontal Mount: 6"(152) - 76"(1930)	
Nominal Duct Height 'H'	Damper Height 'T'
46"(1168)	51"(1295)
47"(1194)	52"(1321)
48"(1219)	53"(1346)
49"(1245)	54"(1372)
50"(1270)	55"(1397)
51"(1295)	56"(1422)
52"(1321)	57"(1448)
53"(1346)	58"(1473)
54"(1372)	59"(1499)
55"(1397)	60"(1524)
56"(1422)	61"(1549)
57"(1448)	62"(1575)
58"(1473)	63"(1600)
59"(1499)	64"(1626)
60"(1524)	65"(1651)
61"(1549)	66"(1676)
62"(1575)	67"(1702)
63"(1600)	68"(1727)
64"(1626)	69"(1753)
65"(1651)	70"(1778)
66"(1676)	71"(1803)
67"(1702)	72"(1829)
68"(1727)	72"(1829z)
69"(1753)	74"(1880)
70"(1778)	75"(1905)
71"(1803)	76"(1930)
72"(1829)	77"(1956)
73"(1854)	78"(1981)
74"(1880)	79"(2007)
75"(1905)	80"(2032)
76"(1930)	81"(2057)
77"(1956)	82"(2083)
78"(1981)	83"(2108)
79"(2007)	84"(2134)
80"(2032)	85"(2159)
81"(2057)	86"(2184)
82"(2083)	87"(2210)
83"(2108)	88"(2235)
84"(2134)	89"(2261)
85"(2159)	90"(2286)
86"(2184)	91"(2311)
87"(2210)	92"(2337)
88"(2235)	93"(2362)
89"(2261)	94"(2388)
90"(2286)	95"(2413)
91"(2311)	96"(2438)

NOTE:

Dampers in the grey shaded area are for Vertical Mount Only".

Dampers shown as Vertical Mount. Horizontal Mount supplied in the same orientation.