





FD-4-IMB
(standard)


[†]Damper dimensions furnished approximately 1/8" (3) undersize.

Options

- **Alternate sleeve/frame length:**
 - 16" (406) ▪ Other _____
- **Transitions:**
 - Round ▪ Oval
 - Duct connections (sleeve required):
 - 1" (25) S-clip ▪ DM-25 ▪ DM-35 ▪ WARD
- **Alternate fire closure temperature:**
 - 212°F (100°C)
- **Generic mullion for oversized masonry or concrete openings**
- **PI-10** (Blade closure indication switch package):
 - External mount (sleeve required) ▪ Internal mount ▪ Loose



Type BR (Optional)
Round duct transitions are standard with D=W=H. (available with D<W and H)



Type BO (Optional)
Oval duct transitions are standard with W and H equal to damper width and height dimensions. (available with W and H smaller than damper width and height)

The FD-4-IMB fire damper employs out of the air stream curtain style blades and a factory installed integral mounting angle for ease of installation and point-of-origin control of fire in static HVAC systems. The integral mounting angle is designed and approved to be fastened directly to the fire separation and may be installed under the drywall in metal stud construction. The FD-4-IMB may be installed in vertical walls or partitions with fire resistance ratings up to 2 hours.

Ratings

UL 555 Fire Resistance Rating: 1-1/2 Hour (vertical)

Listings

UL 555 listing: R14981

CAN/ULC S112 listing: R14981

CSFM listing: 3225-1404:101

New York City MEA listing: 295-98-E

Meets NFPA Standards: 90A, 92A, 92B and 101

Meets Building Code Standards: IBC, NBC, NFPA, SBC and UBC



Standard Construction

Sleeve/Frame: Integral 12" × 20 gauge (305 × 1.0) galvanized steel with 1-1/2" × 20 gauge (38 × 1.0) galvanized steel integral single side mounting angle

Blades: 24 gauge (0.7) galvanized steel – curtain style

Fire Closure Device: UL listed fusible link

Fire Closure Temperature: 165°F (75°C)


Minimum Size: 4" × 2" (102 × 51)

Maximum Size: 48" × 44" (1219 × 1118)

Blade Stack Dimensional Data

FD-4-IMB

1-1/2 Hour Dynamic Rated – Fire Damper
Integral Mounting Angle – Curtain Style Blade



Nominal Duct Height 'H'	Damper Height 'T'
2" (51)	4" (102)
3" (76)	5" (127)
4" (102)	6" (152)
5" (127)	7" (178)
6" (152)	8" (203)
7" (178)	9" (229)
8" (203)	10" (254)
9" (229)	11" (279)
10" (254)	12" (305)
11" (279)	13" (330)
12" (305)	14" (356)
13" (330)	15" (381)
14" (356)	16" (406)
15" (381)	17" (432)
16" (406)	18" (457)
17" (432)	19" (483)
18" (457)	20" (508)
19" (483)	21" (533)
20" (508)	22" (559)
21" (533)	23" (584)
22" (559)	24" (610)
23" (584)	25" (635)
24" (610)	26" (660)
25" (635)	28" (711)
26" (660)	29" (737)
27" (686)	30" (762)
28" (711)	31" (787)
29" (737)	32" (813)
30" (762)	33" (838)
31" (787)	34" (864)
32" (813)	35" (889)
33" (838)	36" (914)