




SD-182-SS
(standard)

*Damper dimensions furnished approximately 1/4" (6) undersize.
(sleeve thickness not included)

Options

- **Alternate actuator:**
 - Internal mount (actuator in air-stream)
 - 24 VAC ▪ 230 VAC
- **PI-50 — Dual position indicator switch package**
- **Factory-installed sleeve:**
 - Type: ▪ A (Std.) ▪ C
 - Gauge: ▪ 20 (0.91) ▪ 18 (1.3) ▪ 16 (1.6) ▪ 14 (2.0)
 - 10 (3.4)
 - Length: ▪ 12" (305) ▪ 16" (406) ▪ 20" (508)
 - 24" (610) ▪ Other _____
 - No Sleeve (Actuator must be internally mounted)
- **Transitions:**
 - Flanged ▪ Round ▪ Oval
 - Duct connections:
 - DM25 ▪ DM35 ▪ DM45 ▪ Ward
- **Retaining angle systems:**
 - Gauge: ▪ 16 (1.6)
 - Individual angle sets: ▪ DS (2-sided) ▪ SS (single-sided)
- **Duct smoke detector factory mounted and wired:**
 - D4120 (100-4,000 fpm [0.5-20.3 m/s])
 - 2151 (0-3,000 fpm [0-15.2 m/s])
- **Duct access door factory mounted in common sleeve**
- **Remote control stations:**
 - RCP-1 (single) ▪ RCP-1K (single, key controlled)
 - RCP-1M (single, momentary switch)
- **Remote light panel**

The SD-182-SS smoke damper employs 304 stainless steel air-foil blades for point-of-origin control of smoke in static and dynamic smoke management systems. The SD-182-SS is qualified to 2,000 ft/min (10.16 m/s) and 4 in.wg. (1.0 kPa) and may be installed in vertical walls or partitions.

Ratings

- UL 555S Leakage Class:** 2 [20 cfm/sq.ft. @ 4 in.wg.]
[(0.10 m³/s/m² @ 1.0 kPa)]
- Maximum Dynamic Closure Velocity:** 2,000 fpm (20.3 m/s)
- Maximum UL555S Rated Pressure:** 4 in.wg. (2.0 kPa)
- Maximum Temperature:** 350°F (177°C)

Listings

- UL 555S listing:** R14981
- CAN/ULC S112 and CAN/ULC S112.1 listing:** R14981
- CSFM listing:** 3225-1404:107
- New York City MEA listing:** 295-98-E
- Meets NFPA Standards:** 90A, 92A, 92B and 101
- Meets Building Code Standards:** IBC, NBC, NFPA, SBC and UBC



Standard Construction

- Frame:** 5" x 1" (127 x 25) stainless steel hat channel with interlocking corner gusset. Equivalent to 13 gauge (2.4) channel frame. Low profile head and sill are used on sizes less than 13" (330) high.
- Blades:** 6" x 14 gauge (152 x 2.0) equivalent stainless steel airfoil
- Side Plate:** 12" x 20 gauge (305 x 1.0) stainless steel
- Axles:** 1/2" (13) diameter stainless steel hex
- Linkage:** Concealed in frame
- Bearings:** Stainless steel oilite, sleeve-type
- Seals:** Silicone blade edge seals integrally rolled and mechanically fastened to blades. Flexible metal jamb seals
- Actuator:** 120 VAC, power-open, spring-close, external mount
- Minimum Size:** 8" x 6" (203 x 152)
Type C: 6" x 4" (152 x 102)
- Maximum Size:** Single section: 24" x 36" (610 x 914)
Type C: 22" x 34" (559 x 864)
Multiple section: Vertical: 96" x 72" (2439 x 1829)
192" x 36" (4876 x 914)


NOTE: Dimensions in parentheses () are millimeters.
Information is subject to change without notice or obligation.

Actuator and Sleeve Dimensional Data

SD-182-SS

1-1/2-Hour fire • UL Class 2


Smoke Damper • Stainless Steel - Airfoil Blade



Sleeve (Optional)


Type R (Optional)

Round duct transitions are standard with $D=W=H$.
(available with $D<W$ and H)



Type O (Optional)

Oval duct transitions are standard with W and H equal to damper width and height dimensions. (available with W and H smaller than damper width and height)





Type C (Optional)

Damper is oversized and uses rectangular transitions to remove damper frame from airstream

*Damper dimensions furnished approximately 1/4" (6) undersize.
(sleeve thickness not included)

The drawings and corresponding table illustrate the position of the damper and the relative space required for a given actuator. The standard mounting locations provide enough space for installation of retaining plates and duct connections.

Actuator Model			
	Damper Height	FSLF120 FSLF24	FSNF120 FSNF24
F	6"-7"	5"	7"
	8"-9"	4"	7"
	10"-11"	1"	4"
	12"-13"	0"	3"
	14"	0"	2"
	15"-16"	0"	1"
	17"	0"	3"
	18" and 23"	0"	0"
	19"- 20" and 25"	0"	0"
T	21"- 22" and 24"	0"	0"
	26"-27"	0"	0"
	>27"	0"	0"
	6" and 10"	3"	3"
	7" and 11"- 12"	2"	2"
	8", 13", -14" and 21"	1"	1"
S	9", 15"-17" and 20"	0"	0"
	18"- 19"	0"	1"
	22"-23" and >24"	0"	0"
	24"	0"	0"
X	All	4-1/2"	4-1/2"
J	<8"	4"	4"
	≥8"	2-5/8"	2-5/8"
	<8"	2"	2"
	≥8"	3-3/8"	3-3/8"





- NOTE:**
1. Sleeve length "L" = wall/floor thickness + 10" (254). Standard sleeve length "L" = 16" (406)
 2. Damper may be rotated 180° to position actuator area on the left side.
 3. The entire damper frame is not required to be installed within the wall, partition or floor. However, the closed plane of the damper blades must be inside the wall, partition or floor.
 4. For dimensions on actuators not shown above, contact factory.

Pressure Drop Performance Data

Pressure Loss vs. Velocity



Figure 5.3 — Ducted Inlet and Outlet



Ducted Inlet and Outlet

AMCA Figure 5.3 illustrates a fully ducted damper. This configuration represents the lowest pressure drop of the three test configurations because entrance and exit losses are minimized by straight duct runs upstream and downstream of the damper.



Figure 5.2 — Ducted Inlet



Ducted Inlet

AMCA Figure 5.2 illustrates a ducted damper exhausting air into an open area. This configuration has a lower pressure drop than Figure 5.5 because entrance losses are minimized by a straight duct run upstream of the damper.

Figure 5.5 — Plenum Mount



Plenum Mount

AMCA Figure 5.5 illustrates a plenum mounted damper. This configuration has the highest pressure drop because of extremely high entrance and exit losses due to the sudden changes of area in the system.